


TECHNICAL SPECIFICATIONS

MODEL	u.m.	330	510
Capacity			
1 st speed	m³/h	1400	2100
2 nd speed	m³/h	2400	3600
3 rd speed	m³/h	3400	5100
Noise			
1 st speed	dB	43	43
2 nd speed	dB	45	47
3 rd speed	dB	54	56
Consumption	W	190	255
Power input	V-Hz	230 - 50/60	230 - 50/60
Dimensions AxBxC	mm	1320x468x303	1920x468x303
Dimensions AxBxC	mm	468x303x1480 (wheel-mounted)	468x303x2080 (wheel-mounted)
Weight	Kg	54	75
Weight	Kg	56 (wheel-mounted)	78 (wheel-mounted)
Cells	n°	2	3
Installation		ceiling, wall, wheels	ceiling, wall, wheels
Remote control		yes	yes

MONOLITE SERIES

330
510

CEILING- OR WALL-MOUNTED MODEL



WHEEL-MOUNTED

CERTIFICATIONS



MONOLITE

330
510



DESCRIPTION

The MONOLITE series was initially designed for the service sector but it is also suitable for large residential areas. Not only does MONOLITE purify the air but it also improves breathing; MONOLITE is a synonym for hygiene, prevention, well-being and comfort. Its extremely low noise levels makes it go by almost unnoticed while its sturdy construction, the use of high quality materials and its outstanding performance levels make it an attractive and reliable product; a unique market benchmark. The MONOLITE series comprises two models whose convenience and versatility are immediately evident. Special installation kits allow these models to be mounted on walls and ceilings, or, for more demanding customers, on wheels so that they can be easily moved from one room to another without the need for installation. All the versions are supplied standard with a user-friendly remote control unit.

AIR HANDLING
SOLUTIONS

TECHNOLOGIES

OUR THREE LEVELS OF TECHNOLOGY



NATURE SYSTEM®

NATURE SYSTEM® technology incorporates the most complete and evolved air treatment system, as can be found in the RIVITALIZZATORE®.

Given that the atmosphere contains a variable number of sources of pollution, with the RIVITALIZZATORE® the daytime or night-time operating cycle can be selected.

After the operating function has been set, it can automatically control and manage all the operating phases required to achieve the finest air quality. In the daytime cycle, it alternates the purification phase with the revitalisation phase at regular intervals, programmed according to operating speed, while in the night-time cycle just the revitalisation phase is performed. The control panel constantly displays the function performed and reports any faults and when maintenance is required.

If filtration is not ideal during the daytime cycle, the system automatically activates the ventilation only phase and disables all the others.

The RIVITALIZZATORE® is ideal for city dwellers who wish to experience the emotion of breathing air that is similar to that in natural uncontaminated environments.



AFC SYSTEM®

In air purification, AFC® technology symbolises the tradition of EXPANSION ELETRONIC.

Its microprocessor independently controls the performance of the electrostatic cell that automatically adjusts the filtration level to the specific operating condition.

The information is managed via the control panel. This makes it possible to change the conditions of use at any time, report any faults and signal when the electrostatic cells must be cleaned. To protect the electronic parts of the machine and constantly assure total reliability, the system automatically stops if the required operation is not performed.

In other words, the AFC® system guarantees that optimal performance is constantly maintained whilst minimising external interventions.


All the user has to do is to switch on and select the most appropriate speed for his/her requirements because everything else is done by the machine.



BASIC SYSTEM

BASIC SYSTEM technology identifies traditional air purification systems with electrostatic filters. This technology is used by all the manufacturers in the sector. Unlike other technologies, its efficiency is not constant as the dirtier the filter gets, the more air filtering performance level lowers, though this takes place gradually.

This technology is the simplest and earliest version of electrostatic filtration and works with standard applications and management systems. The information managed by the electronic circuit and displayed on the control panel only shows the basic functions.



PERFORMANCE 330 - 510



EQUIPMENT, PERFORMANCE AND CONTROLS	NATURE SYSTEM®	AFC SYSTEM®	BASIC SYSTEM
Built-in humidity sensor		-	-
Dual voltage electrostatic filtering (by Expansion Electronic)			
CPU for real-time function management			-
Filtering performance control and management			-
Control and management of automatic daytime ionic balance (ideal microclimate)		-	-
Control and management of night-time deodorisation with negative ions		-	-
Control and management of the reduction in the daytime environmental bacterial level	-77%	-55%	-30%
Control and management of the reduction in the night-time environmental bacterial level	-92%	-	-
Control and management of the reduction in daytime and night-time environmental mould	-98%	-40%	-32%
Control and management of the reduction in environmental electrostatic charges	-99%	-	-25%
Control and management of ozone emissions according to EN60335-2-65:2003-07	<1 ppm (limit 5ppm)	<1 ppm (limit 5ppm)	<1 ppm (limit 5ppm)
Automatic control and management of the quantity of daytime negative ion emissions		-	-
Automatic control and management of the quantity of night-time negative ion emissions		-	-
Performance tolerance	±1%	±1%	±9%
Activation of functions using the IR remote control			
Automatic restart following a power blackout			
Control LED check-up button			-
Alarm light for routine maintenance			
Pre-alarm light for routine maintenance			-
Fault warning light			
Filtration performance warning light			-
Negative ion emitter electrode/s in special wear-resistant alloy		-	
Assembly kit			
Warranty on electronic components (for manufacturing defects)	3 years	3 years	2 years
Warranty on the motor/s (for manufacturing defects)	3 years	3 years	3 years
1 st speed filtration performance (on PM2.5)	99% constant	99% constant	95% inconstant
2 nd speed filtration performance (on PM2.5)	98% constant	98% constant	89% inconstant
3 rd speed filtration performance (on PM2.5)	96% constant	96% constant	86% inconstant

OPTIONS

- Activated carbon filter;
- Extensive RAL colour range.